

HIGHBAY

LU-HB06 Luciano Highbay light was carefully designed for industrial lighting adopting the neest LED lighting technology, with longer lifespan, lower maintenance cost and higher efficiency. Our highbay is suitable for different kind of projects due to our different choices available: different covers, lenses, reflectors. The mainly application are industrial use like factories or warehouses, but it is also suitable for exhibition halls, showrooms or indoor sports arena. The excellent design with a perfect cooling performance, assures the long lifespan of the electronic components.

Product information

CRI 80 RA

Dimmable 1-10V

DALI

Clear, Milky Cover, Lens Or Al / Pc Reflectors

Microwave Motion Sensor

Emergency

Zigbee



Model No.	LU-HB6-100W	LU-HB6-150W	LU-HB6-200W	LU-HB6-300W
Dimensions(mm)	Ø280x175	Ø320x177	Ø365x180	Ø400x260
Power	100W	150W	200W	300W
Voltage	AC100-277V / 277-480V / 50-60Hz			
CCT	3000K/4000K/6000K			
Luminous Efficiency	130 lm/w / 150 lm/w			
Luminous Flux 130 lm/w	13000lm	19500lm	26000lm	39000lm
Luminous Flux 150 lm/w	15500lm	22500lm	30000lm	45000lm
CRI	Ra > 70 (Ra > 80 optional)			
Beam Angle	standard 110° (with glass cover) / 30° , 60° , 90° (with pc lens) / 60° ,			
	90° (with aluminum reflector) / 90° (with pc reflector)			
IP Grade Protection	IP65			
Fixture material	Die cast aluminum			
Material Diffuser	Clear Polycarbonate			